

# SONGSTAB™ SZ-210

**Components**

Zinc stearate  
 $\text{Zn}(\text{C}_{17}\text{H}_{35}\text{COO})_2$   
Mw : 597

**Properties**

Appearance	White Powder
Moisture (%)	Max. 1.0
Free Acid (%)	Max. 0.5
Oxide (%)	13.5 ~ 14.2
Melting Point (°C)	118 ~ 122

**Characteristics & Usages**

- Applications include PVC film and sheet and Polyolefin stabilization as well as paint dryer, rubber mold release lubricant, and dispersion aid.
- Halogen / Acid Scavenger and Lubricant for Plastics.
- Good clarity and weather ability when used with Ba and epoxy stabilizers.
- Excellent synergistic effects when used with Ca and epoxy stabilizers.
- Very low moisture and free acid content.
- Excellent lubricity for PS applications.
- For additional information please consult the MSDS.

**Physical Form**

PW (Powder)

**Packaging unit**

20 kg Paper Bag

**Disclaimer**

SONGWON provides customers with warranties and representations as to the chemical or technical specifications, compositions and/or the suitability for use for any particular purpose exclusively in individual written agreements. The facts and figures contained herein have been carefully compiled to the best of SONGWON's knowledge but are essentially intended for informational purposes only. SONGWON Industrial Group does not accept any liability whatsoever for any information, reference or advice provided in this document or any similar SONGWON publication.